



FP15P

Large format passive full range speaker



Features

- High-power 2-way PA sound reinforcement speaker system for live and playback applications
- Full size and modest weight system delivers excellent sound even at extreme sound pressure levels
- Extremely Efficient 15" woofer driver provides incredibly deep bass and acoustic power
- Precise 1" compression driver for exceptional high frequency reproduction
- Ultra-wide dispersion
- Versatile trapezoidal enclosure design allows different positioning
- Stand mounting with 35-mm pole socket
- Tilts on its side for use as a floor monitor
- Rugged ABS box provides strength and manageability
- Ergonomically shaped handles for easy carrying and setup
- Designed, engineered and tuned in Italy

Applications

- The FP15P is ideal for mobile and installed applications. It is an excellent choice for a wide variety of applications, including retail stores, restaurants, health clubs, theme parks, educational facilities, hospitality, music cafes, leisure venues, and anywhere where a top quality high output indoor/ outdoor foreground/ background music (and/or paging) speaker is required.

The FROG-IS FP15P is the first choice for demanding musicians and DJs who work in loud environments.

A multi-purpose speaker system, fully equipped to serve as a main PA, a stage monitor, a distributed audio system and also other applications.

The FP15P delivers punchy, assertive sound and very high sound pressure levels when used with FROG-IS FI-AMP8 and FI-AMP4K amplifiers.

Loaded with high quality speakers, it provides premium audio performance with maximum reliability and minimum power compression that is easy to install.

A strong-built and robust construction designed to handle high loads, rendering lead vocals, guitars, electronic instruments, and playback tracks with power and authority, easily delivering sound across medium-to-longer distances.

The FP15P features provide musicians and audiences with an excellent acoustic experience, even on the most demanding stages.



Specifications

Acoustics	
Frequency range	50 Hz - 20 kHz (± 3 dB)
SPL 1W/1mt	102 dB
Maximum SPL	134,8 dB @ 1 m peak
Coverage	
Horizontal	90°
Vertical	50°
Transducers	
Low Frequency	15" woofer
High Frequency	1" compression driver, horn loaded
Physical	
Mounting	Lockable 1-3/8" (35 mm) stand mount
Rigging Inserts	3 points, accepts M8 threaded hardware
Input Connector	1 XLR and 1/4" TRS balanced
Output Connector	1 XLR balanced
Net Weight	19 kg (41.88 lb)
Dimensions W/ H/ D	69 cm x 40 cm x 45 cm (27.16" x 15.74" x 17.71")

