



FI-Mix8

8 channels mixer with digital effects and USB connection



The FI-Mix8 compact mixer has a natural sound with outstanding parameters and optimal user-friendliness as well as maximum dependability in day-to-day operation on the road.

The FI-Mix8 is reliably rugged, with the proven quality you expect from Frog-is. An amazing value, the mixer delivers a straightforward feature set that's easy to use and the sound quality you need in rugged designs built to last. Plus, with its rugged metal chassis and high-quality components throughout, the FI-Mix8 is a solid investment in reliability.

Product Features

- 8 mono channels input
- 2 main outputs, 1 channel MP3 output, 1 Aux output
- USB Player, Bluetooth connection, Recording function
- Global +48V phantom power for condenser microphones
- Control room/Phones source matrix for monitor flexibility
- Input channels with 3-band EQ, 45mm faders, main output 60mm faders
- Especially high headroom and dynamic range
- Extra low-distortion preamps
- Robust construction for long service life

Product Applications

Whether live on stage, home/project recording or installations of all kinds such as community centers, churches, and bars/bistros, the FI-Mix6 offers the right solution for many applications.



Product Specification

Mic Input (Mono)	
Main Mix Noise	-86.5 dBu
THD	<0.0007%
Attenuation	Channel Mute switch engaged: -82 dBu Channel Gain knob down: -82 dBu
Frequency Response	20 Hz to 40 kHz: +0 dB/-1 dB 20 Hz to 60 kHz: +0 dB/-3 dB
EQ	High Shelving: +15 db @ 12 kHz Mid Peaking: +15 dB sweep 100 Hz-8 kHz Low Shelving: ±15 db @ 80 Hz Low Cut Filter: 18 dB/octave, -3 dB @ 75 Hz
Equivalent Input Noise	1 50 ohm termination: -129.5 dBu20 Hz-20 kHz
Common Mode Rejection Ratio	1 kHz: better than -70 dB
Maximum Levels	Mic in: +22 dBu All other inputs: +22 dBu Main Mix TRS out and XLR out: +28 dBu All other outputs: +22 dBu
Impedances	Mic in: 2.5 kilohms Channel Insert return: 2.5 kilohms All other inputs: 10 kilohms or greater Tape out: 1.1 kilohms All other outputs: 120 ohms
Power Consumption	120/240 VAC,50/60 Hz. 50 watts
Net weight:	3.7 kg
Packing weight:	4.55kg
Net Dimension:	39x32x8.5 cm
Package Dimension:	42x41.5x13.5 cm

