

FI-SMS4 (B/W)

Two-way Surface Mounted



Features

- Two-way speaker with rich sonic character
- Wide and consistent coverage
- Suitable for high (70/100 V) voltage line and low impedance (8 Ω) installations
- Contemporary, high-design appearance
- High fidelity sound character with broad frequency response of 90 Hz - 20 kHz.
- High quality speaker enclosures made of strong ABS material
- Heavy-duty C-bracket for mounting included
- Easy installation

Applications

The FI-SMS4 is an excellent choice for a wide variety of applications, including retail stores, restaurants, health clubs, theme parks, educational facilities, hospitality, music cafes, leisure venues, and anywhere where a top quality high-output indoor/outdoor foreground/ background music (and/or paging) speaker is required.

The elegant design allows the FI-SMS4 to be used for any installations and environment, keeping the same high quality sound throughout.

The FI-SMS4, made of ABS with a front metal grille, utilizes a compact two-way system (4" woofer, 1" tweeter) guaranteeing high performances, wide dynamics, high fidelity sound reproduction and high voice intelligibility.

Multi-position, C-shaped mounting bracket, and rugged construction provide optimum installation flexibility and assurance of long-term service.

Its power tap selector makes it suitable for high (70V/100V) voltage line and low impedance (8 Ω). This ceiling speaker is designed to offer an economic and professional solution to contractors.





Specifications

| General Specification | |
|------------------------------|---------------------------------------|
| type | FI-SMS4 (B/W) |
| Frequency response | 90 -20 KHz |
| Sensitivity | 89dB @ 1 watt / 1 meter |
| Power Handling | 20 W |
| Power taps | 20W/10W/5W/2,5W & 8Ω |
| Line input | 100 V / 70 V |
| Dimension (L x W x H) (mm) | 130*125*210 |
| Physical Specification | |
| Material (panel) | HIPS |
| Grille | Powder Coated AL Mesh |
| Component (L.Speaker) | 4» PP Woofer |
| Component (H.Speaker) | 1» PEI |
| Finished Colour | White/Black |
| Unit Weight | 2.1 Kg |
| Woofer Speaker Specification | |
| Voice Coil Size | ø 0.15*2Layer |
| DC Impedance | 7,2Ω |
| Former | Asv |
| Magnet | Ferrite (416g) ø 80*ø 32*15(Y30) |
| Basket | Iron |
| Cone Material | PP |
| Spider | Cloth |
| Dust cap | РР |
| Net Weight | 685 g |
| | · · · · · · · · · · · · · · · · · · · |







