



FI-SUB10A

Compact Cubic Active Subwoofer



The FI-SUB10A is an ultra-compact cubic active subwoofer dedicated to the installation market.

The front firing 10" woofer is back loaded by two side 10" passive radiators, providing an extreme low frequency extension for its modest size.

Product Features

- Extreme discreet look
 - Extreme low-end extension
 - High efficiency, allowing supporting multiple full range installation speakers
 - Ideal for outdoor installation applications
 - High power 200W Class AB amplifier
- Multiple controls allowing adjusting of level, LPF frequency and phase

Products Applications

- Ideal for larger size cafés, restaurants, lounges, churches
- Ideal for home theatre



Product Specification

Acoustic properties	
Frequency Response	40 Hz - 150 Hz
Power	250 Watts
SPL 1W/1mt	114dB Cont. – 120dB Peak
Impedance	4 Ohms
Speaker unit	1 x 10" subwoofer and 2 x 10" passive units
Built-in amplifier	
Voltage	Fixed 110V or 220V
Operating Voltage	110V (100V to 125V) 220V (200V to 245V)
Maximum output 1% THD	200 Watts @ 4 Ohms
Protection	short circuit, overheating, overload
Physical	
Weight	15.7 kg (34.5 lb)
Dimensions Width/Height/Length	32 cm x 36 cm x 33 cm (12.6" x 14" x 13")