

FI- SUB6P

Ultra Compact Installation Sub-woofer



The FI-Sub6P is an Ultra-compact Passive 6" Subwoofer.

The 6" passive radiator emulates a larger internal volume giving this tiny sub the deep bass performance of a Sub-woofer three times its size.

Features

- Ultra-compact installation subwoofer
- Designed, engineered and tuned in Italy
- The enclosure made of Stainless Steel, giving an IP54 rating
- Ideal for outdoor installation applications
- Compact and discrete, making it ideal for sophisticated interior designs
- Impressive Low frequency performance for its minimal size





Applications

An excellent solution to fulfil any installation applications such as restaurants, lounges, hotel lobbies, corporate offices, retail store, outdoor terraces etc.



B2, 5/f, Mai Hing Ind'l Bldg Block B, 16-18 Hing Yip Street, Kwun Tong, Kowloon, Hong Kong Tel: +86 574 8757 6644 — Fax: +86 574 8757 6884

Specifications

General specifications	
Acoustic Concept	Passive Radiator loaded.
Electrical Concept	Dynamic, dual 4 Ohms Voice Coils.
Impedance	Selectable, 2 Ohms, 4 Ohms, 8 Ohms.
Frequency Response	40Hz to 140Hz (-6dB).
Efficiency	91dB / 1W / 1M
Maximum SPL	106dBC Cont. / 112dBC Peak.
Transducers	6" Dynamic Woofer with dual 1.5" Voice coil
	Single 6" Passive Radiator
Power Handling	200 Watts Avg. (2 x 100 Watts)
Connector	Phoenix, 4 contacts.
Enclosure	Stainless Steel, Weather Resistant, IP54.
Dimensions	Triangular, 20cm W, 20cm D, 20cm H.
Weight	4.6 Kg

