



FI-CSub6P

Compact passive 6" ceiling mount subwoofer



The FI-CSub6P is a compact passive 6" ceiling mount subwoofer.

The FI-CSub6P comes standard with an "Acoustic Back Loading Enclosure".

It's overall size is the one of a standard 6" ceiling speaker.

The 6" woofer is the same as our surface mount FI-Sub6P, but it has a dual acoustic port system making it a perfect Bass Reflex loading system.

The FI-CSub6P provides the equivalent punch of a floor standing Sub-woofer.

Product Features

- Compact and discrete, making it ideal for sophisticated interior designs
- The 6" woofer is designed, engineered and manufactured in Italy
- Ideal for installation where the designer will not allow any surface sub-woofer
- Impressive Low frequency performance for it's minimal size
- 8 Ohms impedance allowing up to two sub-woofer per amplifier channel

Products Applications

An excellent solution to fulfill installation applications such as restaurants, lounges, hotel lobbies, corporate offices, retail stores, etc.



Product Specification

General Specification	
Acoustic concept	Ported bass reflex
Electrical concept	Dynamic, dual 4 Ohms voice coils
Impedance	Fixed 8 Ohms
Frequency response	45Hz to 140Hz (-6dB)
Efficiency	90dB / 1W / 1M
Maximum SPL	104dBC Cont. / 110dBC Peak
Transducer	6" Dynamic woofer with dual 1.5" Voice coil
Power handling	100 Watts avg.
Connector	Phoenix socket
Enclosure	Metal enclosure
Hole for mounting (mm)	ø 240
Dimensions (L x H)	ø 267 x 162 mm
Weight	4.3 Kg

