



FI-Sub12A

12" Active Sub-woofer w/ 2 x 12" passive Radiators,
350W Amplifier



The Fi-Sub12A is an ultra-compact cubic active subwoofer dedicated to the installation market.

The front firing 12" woofer is back loaded by two side 12" passive radiators, providing an extreme low frequency extension for it's modest size.

Product Features

- Extreme discreet look
- Extreme low-end extension
- High efficiency, allowing supporting multiple full range installation speakers
- High power 350W Class AB amplifier
- Multiple controls allowing adjusting of level, LPF frequency and phase

Products Applications

- Ideal for larger size cafés, restaurants, lounges, churches
- Ideal for home theatre



Product Specification

Acoustic	
Frequency Response	35 Hz - 250 Hz
Power handling	350W
SPL @ 1W @ 1M	117dB Cont. - 123dB Peak
Impedance	4 Ohms
Transducers	12" with dual passive radiator
Amplifiers	
Power Voltage	Fixed 110V - 240V
Operating Voltage	110V (100V to 125V) 220V (200V to 245V)
Maximum output 1% THD	350 Watts @ 4 Ohms
Protection	Short Circuit, Thermal, Overload
Physical	
Net Weight	18.5 Kg (40.78 lb)
Dimensions WxHxD	40 cm x 40 cm x 40 cm (15.7" x 15.7" x 15.7")

