



FI-CS2W

Ultra compact ceiling speaker



Product Features

- High performance compact size ceiling speaker for commercial audio applications
- Super high performance 2 inch full range driver for excellent sound quality
- Full protection of the transformer
- Easy, fast and safe fastening system
- Suitable for high impedance (70/100 V) voltage line and low (8Ω) installations
- High resistant ABS housing that protects it from heat and ensure long lifetime
- Suitable for paging and background music applications

Products Applications

- The ceiling speaker is ideal for applications where excellent sound quality is needed for small- volume music playback and paging, such as in music cafes, retail stores, airports, reception / waiting rooms, lounges, courtrooms, convention centers, hotels, educational facilities and more.

The ceiling speaker FI-CS2W is white, with an ABS housing and metal protecting grille.

The Ultra compact size and discreet design and good reproduction of music enable it to fit perfectly into any architectural environment. The built-in transformer enables it to be connected to constant voltage lines with variable power.

The FI-CS2W is an ultra compact size ceiling speaker with high efficiency 2 inch full range driver. It provides high sound quality in your installation.

Its power tap selector makes it suitable for high (70V/100V) voltage line and low impedance (8Ω). The transformer is contained within a metal can enclosure to improve response.

This ceiling speaker is designed to offer an economic and professional solution to contractors.



Product Specification

Comprehensive parameters	
Type	FI-CS2W
Frequency Response	120 -20 KHz
Sensitivity	87 dB @ 1 w / 1 meter
Max SPL	91dB @ 100V 3W
Power taps	6W/3W/ 100V
Rated power	6W @ 8 Ω
Line input	100 V / 70 V; 8 Ω
Hole for mounting (mm)	ø95mm
Dimensions (L x H)	ø103 x 80 mm
Physical Specification	
Material (panel)	Metal frame
Grille	Powder Coated Iron Mesh
Component (L.Speaker)	2" full range driver
Finished Colour	White RAL 9016
Unit Weight	400 g
Gross Weight	12 Kg / 24pcs
Packing Dimension	46 x 35 x 21 cm
Speaker parameters	
Voice Coil Size	ø 0.09"2Layer
DC Impedance	7.2Ω
Magnet	Ferrite (105g) ø 60*ø 24*8(Y30)
Basket	Iron
Cone Material	PCK + PF
Spider	CONEX
Net Weight	220g

