



FI-SMS6(PRO)

Two-way surface mounted speaker with two radiator



The elegant design allows the FI-SMS6(PRO) to be used for any installations and environment, keeping the same high quality sound throughout.

The FI-SMS6(PRO), made of ABS with a front metal grille, utilizes a compact two-way system (6" woofer, 1" tweeter and two passive radiator) guaranteeing high performances, wide dynamics, high fidelity sound reproduction and high voice intelligibility.

Multi-position, C-shaped mounting bracket and rugged construction provide optimum installation flexibility and assurance of long-term service.

Its power tap selector makes it suitable for high (70V/100V) voltage line and low impedance (8Ω). This surface mounting speaker is designed to offer an economic and professional solution to contractors.

Product Features

- Two-way speaker with rich sonic character
- Two passive radiator for ultimate low frequency response
- Wide and consistent coverage
- Suitable for high (70/100 V) voltage line and low impedance (8Ω) installations
- Contemporary, high-design appearance
- High fidelity sound character with broad frequency response of 50 Hz - 20 kHz.
- High quality speaker enclosures made of strong ABS material
- Heavy-duty C-bracket for mounting included
- Easy installation
- Waterproof grade IPX56

Products Applications

- The FI-SMS6(PRO) is an excellent choice for a wide variety of applications, including retail stores, restaurants, health clubs, theme parks, educational facilities, hospitality, music cafes, leisure venues, and anywhere where a top quality high-output indoor/ outdoor foreground/ background music(and/or paging) speaker is required.



Product Specification

Comprehensive parameters	
Product name	FI-SMS6 (PRO)
Frequency Response	50 -20 KHz
Sensitivity	93dB @ 1 watt / 1 meter
Power	80 W
Adjustable Power	80W/40W/25W/10W & 8Ω
Transformer input	100 V / 70 V
Dimensions (W x H x L)	344.5*220*227.3mm
Physical	
Material(panel)	HIPS
Grille	Powder Coated AL Mesh
LF-Driver	6.5 inch Woofer
HF-Driver	1 inch silk
Color	White/Black
Weight	4.3 Kg
Speaker parameters	
Coil size	ASVø25.5*ø 0.19*2Layer
DC resistance	6.8Ω
Model	Asv
Magnet	Ferrite (400g) ø 90*ø 32*15(Y30)
Bracket	Iron
Cone	Paper
Spider	Conex
Dust cover	Paper
Weight	1.1kg

