

## FI-CS5W Two-way ceiling speaker



The ceiling speaker FI-CS5W is white, with an ABS housing and metal protecting grille.

The simple and discreet design and good reproduction of both speech and music enable it to fit perfectly into any architectural environment. The built-in transformer enables it to be connected to constant voltage lines with variable power.

The FI-CS5W is a ceiling speaker with separate woofer and tweeter. It provides high sound quality in your installation.

Its power tap selector makes it suitable for high (70V/100V) voltage line and

Low impedance (8 $\Omega$ ). The transformer is contained within ABS plastic can enclosure to improve response.

This ceiling speaker is designed to offer an economic and professional solution to contractors.

## Product Features

- Two-way ceiling speaker for commercial audio applications
- Separate woofer and tweeter for excellent sound quality
- Full protection of the transformer
- Convenient magnetic front Grill
- Easy, fast and safe fastening system
- Suitable for high impedance (70/100 V) voltage line and low (8 $\Omega$ ) installations
- High resistant ABS housing that protects it from heat and ensure long lifetime
- Suitable for paging and background music applications

## **Products Applications**

 The ceiling speaker is ideal for applications where excellent sound quality is needed for mediumvolume music playback and paging, such as in music cafes, retail stores, airports, reception / waiting rooms, lounges, courtrooms, convention centers, hotels, educational facilities and more.



## Product Specification

General Specification	
Туре	FI-CS5W
Frequency Response	50-20 KHz
Sensitivity	90 dB @ 1 watt / 1 meter
Power taps	30/15/8/4W
Rated power	50 W @ 8 Ω
Line input	100 V / 70 V / 8 Ω
Hole for mounting (mm)	ø 175-185mm, Depth 125mm
Dimensions (L x H)	ø 205 x 125 mm
Physical Specification	
Material (panel)	ABS White RAL 9016
Grille	Powder Coated Iron Mesh
Component (L.Speaker)	5.25" (PCK + PF) Woofer
Component (H.Speaker)	1" Silk
Finished Colour	White RAL 9016
Unit Weight	1.75 Kg
Gross Weight	7 Kg/4PCS
Packing Dimension	50 x 25.8 x 31 cm





