



FS-Bracket3

Multi-angle adjustable wall mount speaker bracket



FS-Bracket3 has fast installation, multi-angle adjustable, safe and durable advantage. Suitable for primary small size speaker with back side mounting screw holes: FS2X3, FS4X3

Product Specification

The FS-Bracket3 is a heavy-duty universal speaker wall mount bracket engineered for safe, fast, and flexible installation of professional loudspeakers. Constructed from high-grade cold-rolled steel with a durable black powder-coated finish, this bracket provides exceptional structural strength and long-term reliability in any installation environment.

Featuring a user-friendly design with multi-angle adjustment, the FS-Bracket3 allows precise speaker aiming across six preset angles (-5° , -15° , -25° , -35° , $+20^{\circ}$, $+32^{\circ}$) to optimize coverage in any space. The integrated cable pass-through hole ensures clean, professional cable management, while the bottom hook design provides additional security during installation.

Whether installed in conference rooms, auditoriums, retail spaces, restaurants, or residential settings, the FS-Bracket3 delivers a secure mounting solution that combines robust construction with effortless installation flexibility.

Product Features

- **Cold-Rolled Steel Construction:** High-grade cold-rolled steel body provides exceptional strength and durability for safe, long-term wall mounting.
- **Multi-Angle Adjustment:** Six preset angle positions (-5°, -15°, -25°, -35°, +20°, +32°) for precise speaker aiming and optimal coverage.
- **Fast & Secure Installation:** User-friendly design enables quick, safe wall mounting with minimal tools required.
- **Integrated Cable Pass-Through:** Built-in cable hole allows clean, concealed cable routing for a professional finish.
- **Bottom Hook Design:** Convenient hook feature provides additional security and support during installation.
- **Universal Compatibility:** Standard mounting pattern compatible with a wide range of professional loudspeakers
- **Powder-Coated Finish:** Durable black powder coating resists scratches, corrosion, and wear for long-lasting appearance.
- **Precision Engineering:** CNC-machined components ensure tight tolerances and a secure, rattle-free fit.

Products Applications

- Conference rooms and boardrooms
- Auditoriums and lecture halls
- Retail stores and shopping centers
- Restaurants, bars, and cafes
- Hotels and hospitality venues
- Educational facilities and classrooms
- Houses of worship
- Residential home theaters
- Fitness centers and gyms
- Any professional loudspeaker wall-mount installation

Installation Guide

Follow these steps for safe and secure installation of the FS-Bracket3:

Step 1 — Position the Wall Plate: Hold the wall plate against the mounting surface at the desired height and location. Mark the four mounting hole positions (50mm spacing, 10mm holes).

Step 2 — Drill & Anchor: Drill holes at the marked positions. Insert appropriate wall anchors (not included) based on the wall material — concrete, drywall, or wood.

Step 3 — Mount the Wall Plate: Secure the wall plate to the wall using suitable screws (M8 or equivalent). Ensure the plate is level and tightly fastened.

Step 4 — Route Cables: Pass the speaker cable through the integrated cable pass-through hole in the wall plate for a clean, concealed installation.

Step 5 — Attach Speaker: Mount the speaker to the bracket arm using the appropriate hardware. Ensure all connections are secure.

Step 6 — Set Angle: Select the desired angle position (-5°, -15°, -25°, -35°, +20°, or +32°) by aligning the adjustment holes and tightening the locking knob.

Step 7 — Final Check: Verify all fasteners are tight, the speaker is secure, and the cable is properly routed. Test the speaker for any movement or rattling.

Note: Always ensure the mounting surface can support the combined weight of the bracket and speaker. For installations above 3 meters, use safety cables as additional restraint. Do not exceed the rated load capacity.



Product Specification

Technical Specifications	
Model	FS-Bracket3
Product Type	Universal Speaker Wall Mount Bracket
Material	Cold-Rolled Steel
Finish	Black Powder-Coated
Mounting Hole Diameter	Φ10 mm
Bracket Height	100 mm
Side Mounting Hole Spacing	45 mm
Wall Plate Dimensions	90 × 50 mm (H × W)
Wall Plate Hole Spacing	50 mm
Adjustable Angles	-5°, -15°, -25°, -35°, +20°, +32°
Cable Management	Integrated pass-through cable hole
Security Feature	Bottom hook design
Installation	Wall mount, secure & fast
Load bearing	<= 40KG
Horizontal Angle	-40°~ + 40°
Vertical Angle	-5° ~ + 35°

Dimensional Drawings

The FS-Bracket3 features precision-engineered dimensions for straightforward installation. All dimensions are in millimeters (mm).

